

TYTAN 2 | Damp-Proof Tub Lights

TYTAN 2 LED Chemo

- Ingress protection: IP66
- Increased resistance to chemical agents
- Copolyester (PCT-G) diffuser
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: ABS
- Mounting: surface, suspended
- Certificates: HACCP, GREENGUARD



Product number	System performance typ. [W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEL
	■	◆	▲	✕		▶	●
9707■00◆▶-▲✕	28/35/47/69	40 = 4000K		BA = Basic RCR = motion detector LS2 = continuous cabling 3hEM = emergency light 3h	4550-11300	1152 [28/47W] 1432 [35/69W]	A++

Article Number | Explanation

Example: HL-■S-HT●-02◆▲C▶

- HL Series
- System performance typ. [W]
- ◆ Light color
- ▲ Beam characteristic
- Control
- ▶ CRI
- * Dimensions [mm]
- ✕ Equipment

For example: HL

HL Series, D=dimmmable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

TRS-STAR GmbH

Werner-von-Siemens-Str. 1
76297 Stutensee

Development, Planning
and Technical Sales
Dipl. Ing. Frank Werz
T +49 6233 347-125
werz@trs-star.com