

TYTAN 2 | Damp-Proof Tub Lights

TYTAN 2 LED Hall

- Optimized for the lighting of halls with high-bay warehouses
- narrow light distribution 60-90 °
- Ingress protection: IP66
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: PC
- Mounting: surface, suspended



Product number	System performance typ.[W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEL
	■	◆	▲	×		▷	●
9706■00◆▷-▲×	58/72	30 = 3000K 40 = 4000K 50 = 5000K	60=60° 70=70° 90=90°	BA = Basic DA = DALI LS2 = continuous cabling	8200-10400	1152 [58W] 1432 [72W]	A++

Article Number | Explanation

Example: HL-■S-HT●-02◆▲▷

HL	Series
■	System performance typ. [W]
◆	Light color
▲	Beam characteristic
●	Control
▷	CRI
*	Dimensions [mm]
×	Equipment

For example: HL

HL Series, D=dimnable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

TRS-STAR GmbH

Werner-von-Siemens-Str. 1
76297 Stutensee

Development, Planning
and Technical Sales
Dipl. Ing. Frank Werz
T +49 6233 347-125
werz@trs-star.com