

## TYTAN 2 | Damp-Proof Tub Lights

### TYTAN 2 LED ENDURA Minus

- Use at very low temperatures from -40 to + 45 °
- Ingress protection: IP66
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: PC
- Mounting: surface, suspended
- Certificates: PZH, HACCP



Product number	System performance typ. [W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEI
	■	◆	▲	✕		▶	●
9704■00◆▶✕	55/69	40 = 4000K		BA = Basic LS2 = continuous cabling	9050-11300	1152 [55W] 1432 [69W]	A++

### Article Number | Explanation

Example: HL-■S-HT●-02◆▲▶

- HL Series
- System performance typ. [W]
- ◆ Light color
- ▲ Beam characteristic
- Control
- ▶ CRI
- \* Dimensions [mm]
- ✕ Equipment

For example: HL

HL Series, D=dimnable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

### TRS-STAR GmbH

Werner-von-Siemens-Str. 1  
76297 Stutensee

Development, Planning  
and Technical Sales  
Dipl. Ing. Frank Werz  
T +49 6233 347-125  
[werz@trs-star.com](mailto:werz@trs-star.com)