

## TYTAN 2 | Damp-Proof Tub Lights

### TYTAN 2 LED ENDURA Plus

- Use at very high temperatures from -40 to + 60 °
- Ingress protection: IP66
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: PC
- Mounting: surface, suspended
- Certificates: PZH, HACCP



Product number	System performance typ. [W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEL
	■	◆	▲	✕		▷	●
9705■00◆▶✕	28/35/43/49	40 = 4000K		BA = Basic LS2 = continuous cabling	4750-8200	1152 [28/43W] 1432 [35/49W]	A++

### Article Number | Explanation

Example: HL-■S-HT●-02◆▲C▷

HL	Series
■	System performance typ. [W]
◆	Light color
▲	Beam characteristic
●	Control
▷	CRI
*	Dimensions [mm]
✕	Equipment

For example: HL

HL Series, D=dimnable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

### TRS-STAR GmbH

Werner-von-Siemens-Str. 1  
76297 Stutensee

Development, Planning  
and Technical Sales  
Dipl. Ing. Frank Werz  
T +49 6233 347-125  
[werz@trs-star.com](mailto:werz@trs-star.com)